





classiX° all-steel bar clamps

Heat-treated, high carbon Acme threaded spindle is manufactured to offer high load capacity, durability and spatter resistance.



classiX® - Standard pad

A range of clamp sizes and performance characteristics with a field replaceable contact pad.

	Clamping Capacity	Throat Depth	Clamping Force	Approx. Weight	Price
GS12-8K	4"	3 1/8"	550 lbs	1.00 lbs	\$21.31
GS16K	6"	3 1/8"	550 lbs	1.05 lbs	\$23.88
GS20K	8"	4"	880 lbs	1.90 lbs	\$30.75
GS16-12K	6"	4 3/4"	1000 lbs	2.35 lbs	\$37.12
GS25K	10"	4 3/4"	1000 lbs	2.65 lbs	\$41.62
GS30K	12"	5 ½"	1200 lbs	3.95 lbs	\$51.66
GS60K	24"	4 3/4"	1200 lbs	5.25 lbs	\$69.34



classiX® - Heavy duty pad

Designed for heavier applications, the classiX® line with heavy duty pads comes with classic rail profiles and a range of clamp openings that will meet most day to day needs.



	Clamping Capacity	Throat Depth	Clamping Force	Approx. Weight	Price
GSM20	7 1/2"	4 3/4"	2660 lbs	5.20 lbs	\$80.59
GSM25	9"	5 ½"	2660 lbs	5.75 lbs	\$92.13
GSM30	12"	5 ½"	2660 lbs	6.35 lbs	\$99.12
GSM40	16"	5 ½"	2660 lbs	6.70 lbs	\$112.74
GSM50	20"	5 ½"	2660 lbs	7.40 lbs	\$127.84
GSM60	24"	5 ½"	2660 lbs	8.10 lbs	\$145.07







Welding table clamp, variable throat depth, TWV

Precise, individual clamping with variable height and adjustable throat depth. Tempered profile rail and sliding arm for strong, dependable clamping.

Available with: high quality 2-component plastic handle; T-Bar with rounded ends (each with smooth-running ACME threaded spindle and tool free pressure plate replacement); or lever handle with a ratcheting mechanism for controlled, fast and vibration-proof clamping.

	Handle Style	Hole Diameter	Clamping Capacity	Nominal Throat Depth	Rail Profile	Clamping Force	Approx. Weight	Price
TWV16-20-15-2K	Composite	16 mm	8"	1 3/16" - 6"	7/8" - 3/8"	550 lbs	2.50 lbs	\$67.41
TWV16-20-15K	T-Bar	16 mm	8"	1 3/16" - 6"	7/8" - 3/8"	550 lbs	2.34 lbs	\$67.41
TWV16-20-15H	Lever	16 mm	8"	2 %" - 6"	7/8" - 3/8"	550 lbs	2.72 lbs	\$91.78
TWV28-30-17-2K	Composite	28 mm	12"	1 1/16" - 6 1/8"	1 1/8" - 7/16"	1100 lbs	4.89 lbs	\$82.16
TWV28-30-17K	T-Bar	28 mm	12"	1 1/16" - 6 1/8"	1 1/8" - 7/16"	1100 lbs	4.65 lbs	\$82.16
TWV28-30-17H	Lever	28 mm	12"	4 1/16" - 6 1/8"	1 1/8" - 7/16"	1100 lbs	5.47 lbs	\$112.65









Malleable cast, ground clamp

Quick action bar clamp that can also double as a grounding clamp for versatile work across applications. The TP-1K comes with a standard pad and a 10.5 mm grounding connection hole in the fixed jaw.

	Clamping Capacity	Throat Deoth	Clamping Force	Approx. Weight	Price
TP-1K	6"	3 ½"	400	1.65 lbs	\$22.65





Pivot handle clamp, GZ

Premium all-steel clamp with composite swivel handle. Clamp in areas where access is challenging, by folding the handle 90° or rotating it 360°.

	Clamping Capacity	Throat Depth	Clamping Force	Approx. Weight	Price
GZ25PH	10"	4 3/4"	1100 lbs	3.12	\$91.51
GZ30-12PH	12"	4 3/4"	1100 lbs	3.30	\$98.41
GZ40-12PH	16"	4 3/4"	1100 lbs	3.72	\$105.29
GZ50-12PH	20"	4 3/4"	1100 lbs	3.98	\$112.66
GZ60-12PH	24"	4 3/4"	1100 lbs	4.38	\$119.43
3101958	Replaceme	ent handle (h	andle, pad, cap	o)	



Magnetic ground clamps, MGC

Ground clamps only need base surface metal for clamping.

	Pull	Nominal Dimensions	Amps	Approx. Weight	Price
MGC-1	55 lbs	3 1/2" x 2"	250	1.50 lbs	\$35.99
MGC-2	55 lbs	3 1/2" x 2"	800	1.55 lbs	\$43.56





classiX® GSH all-steel lever bar clamps

Quick – up to 5 times faster than regular clamps! Secure, unaffected by vibrations. Strong - high clamping force. Non-slip trigger release. Classic profiled rail.

s \$70.63
s \$82.16
s \$112.41
s \$123.97
_